

Project Name/Reference: _____

Contact Details: _____

VoIP System Manufacturer/Model: _____

VoIP Interface

LAN 1 ☐ VLAN ID (Optional) _____

LAN 2 ☐ VLAN ID (Optional) _____

Note: Only one VLAN available per system.

IP Addresses

LAN 1

Static ☐ DHCP ☐

IP Address _____

Subnet Mask _____

Default Gateway _____

LAN 2

Static ☐ DHCP ☐

IP Address _____

Subnet Mask _____

Gateway _____

VLAN

Static ☐ DHCP ☐

IP Address _____

Subnet Mask _____

Default Gateway _____

DNS

1 _____ 2 _____

Quality of Service (QoS)

Leave blank if QoS not required.

Layer 2

PCP _____ (Default: 3 – Critical Applications)

Layer 3

DSCP – SIP _____ (Default: 24 – Call Signaling)

DSCP – RTP _____ (Default: 46 – Voice)

LLDP-MED

Enable ☐ Disable ☐

If LLDP-MED enabled, check all required fields:

VLAN ID ☐

QoS PCP ☐

QoS DSCP ☐

Inventory ☐

Civic Location ☐

Street _____

Building _____

City _____

State _____

Postal Code _____

Country _____

TransportUDP ☐ TCP ☐ TLS ☐

Listening Port _____

*UDP and TCP Default is 5060, TLS Default 5061***TLS Mode**Always Allow ☐ Always Verify ☐**Local Certificate/Key**Self-Generate ☐ Upload ☐ (Certificate/key must be provided in *.pem format)**Server Certificates***Server certificates (in *.pem format) must be uploaded via the DMP 128 Plus VoIP configuration webpage if TLS mode is set to Always Verify.***Secure RTP (AES CTR)**Enable ☐ Disable ☐**RTP Port Range**

Start Port _____

End Port _____

*Default RTP port range for DMP 128 Plus is 50000 – 50999. Refer to VoIP Configuration Guides for details on how to adjust these values.***NAT Traversal**Disable ☐ STUN ☐ TURN ☐ ICE ☐

STUN Address _____

STUN Port _____

TURN Address _____

TURN Port _____

TURN Username _____

TURN Password _____

Line Configuration

Line _____ of _____

*Complete one Configuration page per VoIP Line***Primary Registration**

Extension _____

Display Name _____

Password _____

Primary Proxy Name/IP _____

Primary Proxy Port _____

Outbound Proxy (Optional)

Outbound Proxy Name/IP _____

Outbound Proxy Port _____

Secondary Registration (Optional)

Secondary Proxy Name/IP _____

Secondary Proxy Port _____

Codecs (check all that apply per line)G.711a ☐ G.711u ☐ G.722 ☐ G.722.1-24 ☐ G.722.1-32 ☐G.722.1c-24 ☐ G.722.1c-32 ☐ G.722.1c-48 ☐ G.726-16 ☐ G.726-24 ☐ G.726-40 ☐G.726-AAL2-16 ☐ G.726-AAL2-24 ☐ G.726-AAL2-32 ☐ G.726-AAL2-40 ☐**DTMF Mode (choose one per line)**In-Band ☐ Out-of-band (RFC 2833) ☐Out-of-band (SIP-INFO Relay) ☐ Out-of-band (SIP-INFO) ☐